RASOTUTTO

- 1. Unique product-type identification code: CEM245
- 2. Type number, batch number, series number or any other element allowing identification of the construction product in accordance with Article 11(4): **RASOTUTTO**
- 3. Intended use or uses of the construction product, in accordance with the relevant harmonized technical specification, as envisaged by the manufacturer: **REGULARISING SKIMMING PLASTER FOR CONCRETE AND HEAT-INSULATING PANELS**
- 4. Name, registered trade name or registered trademark and address of the manufacturer in accordance with Article 11(5)

APSE srl

via Genova 20, 24040 Ciserano (BG) Italia Tel. +39 035/882350 – Fax +39 035/883181 info@apsebg.it <u>www.apse.it</u>

- 5. If appropriate, name and address of the agent whose mandate covers the tasks referred to in Article 12(2): **NOT APPLICABLE**
- 6. System(s) of assessment and verification of constancy of performance of the construction product as referred to in Annex V:

SYSTEM 4

Declared reaction to fire class without the need for testing according to Commission Decision 96/603/EC as amended. In the case of a declaration of performance for a construction product within the scope of a harmonized standard:

NO OBLIGATION OF THE NOTIFIED BODY

7. In the case of a declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

NOT APPLICABLE

8. Declared performance:

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONIZED TECHNICAL SPECIFICATION
Compressive strength	≥ 35 N/mm ²	EN 998-1 (GP)
Bending resistance	≥ 10 N/mm ²	
Resistance to adhesion	≥ 0,5 N/mm ²	
Water vapour permeability coefficient	µ ≤ 10	
Coefficient of thermal conductivity (value of the tabulation)	0,45 W/m•k	
Reaction to fire	Class A1	

9. The performance of the product in items 1 and 2 is in accordance with the declared performance in item This declaration of performance is issued under the sole responsibility of the manufacturer in item 4.

Date of issue: February 2025 Signed for and on behalf of the manufacturer:

