

1. Unique product-type identification code: **RES420**
2. Type number, batch number, series number, or any other element allowing identification of the construction product in accordance with Article 11(4): **HYBRID n-COAT**<sup>®</sup>
3. Intended use or uses of the construction product, in accordance with the relevant harmonized technical specification, as envisaged by the manufacturer: **HYBRID RESIN WITH SUPERIOR QUALITY.**
4. Name, registered trade name or registered trademark and address of the manufacturer in accordance with Article 11(5):

**APSE srl**

via Genova 20, 24040 Ciserano (BG) Italia  
 Tel. +39 035/882350 – Fax +39 035/883181  
 info@apsebg.it [www.apse.it](http://www.apse.it)

1. Where appropriate, name and address of the agent whose mandate covers the tasks referred to in Article 12(2):

**NOT APPLICABLE**

2. System(s) for assessment and verification of constancy of performance of the construction product as referred to in Annex V:

**SYSTEM 4**

3. In the case of a declaration of performance for a construction product within the scope of a harmonized standard:

**NO OBLIGATION OF THE NOTIFIED BODY**

4. In the case of a declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

**NOT APPLICABLE**

5. Declared performance:

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONIZED TECHNICAL SPECIFICATION
Abrasion resistance	Pass	<b>EN 1504-2</b> Coating (C) Principles: (PR)
Capillary absorption and water permeability	$W < 0,1 \text{ kg/m}^2 \cdot \text{h}^{0,5}$	
Impact resistance	Class III	
Direct tensile adhesion strength	$\geq 2,0 \text{ N/mm}^2$	
Release of hazardous substances	See MSDS	

6. The product performance referred to in items 1 and 2 is in accordance with the declared performance referred to in item 9. This declaration of performance is issued under the sole responsibility of the manufacturer in item 4.

Issue date: August 2024

Signed for and on behalf of the manufacturer:

