

1. Unique product-type identification code: **RES560**
2. Type number, batch number, series number, or any other element allowing identification of the construction product in accordance with Article 11(4): **ELASTOTAR**
3. Intended use or uses of the construction product, in accordance with the relevant harmonized technical specification, as envisaged by the manufacturer: **TAR IN WATER EMULSION**.
4. Name, registered trade name or registered trademark and address of the manufacturer in accordance with Article 11(5):

APSE srl
via Genova 20, 24040 Ciserano (BG) Italia
Tel. +39 035/882350 – Fax +39 035/883181
info@apsebg.it www.apse.it

1. Where appropriate, name and address of the agent whose mandate covers the tasks referred to in Article 12(2):
NOT APPLICABLE
2. System(s) for assessment and verification of constancy of performance of the construction product as referred to in Annex V:
SYSTEM 4
3. In the case of a declaration of performance for a construction product within the scope of a harmonized standard:
NO OBLIGATION OF THE NOTIFIED BODY
4. In the case of a declaration of performance concerning a construction product for which a European Technical Assessment has been issued:
NOT APPLICABLE
5. Declared performance:

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONIZED TECHNICAL SPECIFICATION
Permeability to water vapour	$5m \leq S_D \leq 50 m$	EN 1504-2 COATING (C) Principles: MC - IR
Capillary absorption	$W < 0,1 \text{ kg/m}^2 \cdot \text{h}^{0,5}$	
Adhesion by direct traction (without traffic)	$\geq 0,8 \text{ N/mm}^2$	
Direct traction adhesion after thermal shock cycles (without traffic)	$\geq 0,8 \text{ N/mm}^2$	
Reaction to fire	F	
Release of hazardous substances	See MSDS	

6. The product performance referred to in items 1 and 2 is in accordance with the declared performance referred to in item 9. This declaration of performance is issued under the sole responsibility of the manufacturer in item 4.

Issue date: September 2024

Signed for and on behalf of the manufacturer:

