

1. Unique product-type identification code: **RES568**
2. Type number, batch number, series number, or any other element allowing identification of the construction product in accordance with Article 11(4): **APSESHIELD**
3. Intended use or uses of the construction product, in accordance with the relevant harmonized technical specification, as envisaged by the manufacturer: **WATER-REPELLENT TREATMENT BASED ON SILANES AND SILOXANES.**
4. Name, registered trade name or registered trademark and address of the manufacturer in accordance with Article 11(5):

APSE srl

via Genova 20, 24040 Ciserano (BG) Italia
 Tel. +39 035/882350 – Fax +39 035/883181
 info@apsebg.it www.apse.it

1. Where appropriate, name and address of the agent whose mandate covers the tasks referred to in Article 12(2):

NOT APPLICABLE

2. System(s) for assessment and verification of constancy of performance of the construction product as referred to in Annex V:

SYSTEM 4

3. In the case of a declaration of performance for a construction product within the scope of a harmonized standard:

NO OBLIGATION OF THE NOTIFIED BODY

4. In the case of a declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

NOT APPLICABLE

5. Declared performance:

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONIZED TECHNICAL SPECIFICATION
Penetration depth	≥ 10mm (Class II)	EN 1504-2 Hydrophobic impregnation (H) Principles: (PI-MC)
Water absorption and alkali resistance <ul style="list-style-type: none"> • Absorption ratio compared to untreated sample • Absorption ratio after immersion in alkali solution 	≤ 7,5 % ≤ 10 %	
Drying speed	≥ 30 % (Class I)	
Release of hazardous substances	See MSDS	

6. The product performance referred to in items 1 and 2 is in accordance with the declared performance referred to in item 9. This declaration of performance is issued under the sole responsibility of the manufacturer in item 4.

Issue date: November 2025

Signed for and on behalf of the manufacturer:

